

Reasons to choose the MASTER

1 Water Resistant



The concept of a washable hand-held analog unit is exceptional. After measuring, the instrument can be cleaned with running water under a faucet. The new structural-design of these units allows them to be washed whenever necessary. Rated IP65 (dust tight and water resistant).



The world's first feature

2 Hygienic Design



The MASTER series was also designed with a smooth and easy-to-clean grip, eliminating the possibility of food and samples being trapped which can result in contamination and bacterial growth.

3 Visibility



Efficiently using an analog unit depends on how easily the measured value can be read. Extensive research and the use of quality optics result in a measurement scale that is very bright, creating a high contrast to see clearly where the boundary intersects the memory lines of the scale.

4 Automatic Temperature Compensation (ATC)



The newly designed ATC system allows the MASTER series to read more accurately than any comparable unit. ATAGO has applied for a patent on the design of the Improved ATC system. The MASTER series reads more accurately than any comparable unit in the market.

5 Durability



The MASTER series has passed all water resistance, dust resistance, and drop tests. Instruments were subjected to water jets from four directions, dropped from a height of one meter onto an oak platform, and withstood the pressure changes of air travel.

6 Calibration



The α and H types can now be calibrated with the new waterproof calibration screw. All MASTER models can be calibrated by end-user.

7 Automatic Sample Distribution (ASD)



ATAGO has developed a spoon-shaped tip that automatically spreads the sample across the prism. This makes the instrument even more user-friendly, saving valuable time.

8 Repair and Service




ATAGO has established a close network of customers by providing excellent customer service and support. When an ATAGO instrument needs servicing, not only is each customer treated with respect, but they are also provided with detailed methods and userspecific suggestions on sampling and taking measurements, based on individual needs.

9 Reputation for Quality



ATAGO has built a firm reputation for reliability and quality during its over 70 years history. We are a strong company that exports to over 154 countries with continued growth expectations. ISO 9001 certified, along with our integrated system for producing and marketing our products, based on the "Plan-Do-Check-Act" cycle, is essential to the continued quality and to the promoting of the ATAGO name.

Simple Operation



1 Apply 1-2 drops of the sample.

2 Close the daylight plate. View the scale through the eyepiece.

3 Read the measurement value where the boundary line intersects the scale.

Applications

-Measuring sugar concentration, concentration, Brix and Refractive Index-

Honey



Honey

Jam, Syrup



Jam, syrup, confectioneries

Soy milk



Soy milk

Condiments



Condiment, seasonings, ketchup, various sauces, soy sauce

Wine



Grapes, wine must

Drink



Fruit juice, soft drink, carbonated beverage

Cooking



Chinese noodle soup, various soup, various sauces

Agriculture



Fruit and vegetable juice, leaf juice, stem juice, root juice

Salinity



Sodium chloride solution, sea water, pickles

Machine Tools



Firefighting foam, soluble cutting oil

Chemicals and medicine



Brine, deicing solution, medicine, chemical, cosmetics, cleaning solution

Clinical



Urine, serum

Optional Accessories



Daylight Plate
For metal body model
Parts.No. RE-2315-60M
For plastic body model
Parts.No. RE-2315-61M

Small Volume Daylight Plate With Hinge Pin
For metal body model
Parts.No. RE-2311-58M
For plastic body model
Parts.No. RE-2391-50M



Super Extractor
Parts.No. RE-29401



Sucrose solution (for Brix confirmation)
Parts.No. RE-110010 10% Sucrose
Parts.No. RE-110020 20% Sucrose
Parts.No. RE-110030 30% Sucrose
Parts.No. RE-110040 40% Sucrose
Parts.No. RE-110050 50% Sucrose
Parts.No. RE-110060 60% Sucrose

ATAGO CO., LTD.

http://www.atago.net/ overseas@atago.net

ATAGO U.S.A., Inc.
ATAGO INDIA Instruments Pvt. Ltd.
ATAGO THAILAND Co., Ltd.
ATAGO BRASIL Ltda.
ATAGO ITALIA s.r.l.
ATAGO CHINA Guangzhou Co., Ltd.
ATAGO RUSSIA Ltd.
ATAGO NIGERIA Sidemite Co., Ltd.

TEL : 1-425-637-2107
TEL : 91-22-2854915, 40713232
TEL : 66-21948727-9
TEL : 55 16 3913-8400
TEL : 39 02 36557267
TEL : 86-20-38108256
TEL : 7-812-777-96-96
TEL : 234-707-558-1552

customerservice@atago-usa.com
customerservice@atago-india.com
customerservice@atago-thailand.com
customerservice@atago-brasil.com
customerservice@atago-italia.com
info@atago-china.com
info@atago-russia.com
atagonigeria@atago.net

Headquarters: The Front Tower Shiba Koen, 23rd Floor
2-6-3 Shiba-koen, Minato-ku, Tokyo 105-0011, Japan
TEL : 81-3-3431-1943 FAX : 81-3-3431-1945

HACCP GMP GLP

ATAGO products comply with HACCP, GMP, and GLP system standards.

FIAT TECNOLOGIE sas
CORSO NINO BIXIO, 16
12051 ALBA (CN)
TEL 0173 290898 - 366669
FAX 0173 365277
www.fiatalba.it
E-MAIL: info@fiatalba.it
C.FISC. e P.IVA 02713460042
C.C.I.A.A. 33986/1999


* Specifications and appearance are subject to change without notice.

Copyright © 2015 ATAGO CO., LTD. All rights reserved. [ENV.06]15091000PP Printed in Japan



ATAGO
MASTER of REFRACTOMETRY

FIAT TECNOLOGIE sas
CORSO NINO BIXIO, 16
12051 ALBA (CN)
TEL 0173 290898 - 366669
FAX 0173 365277
www.fiatalba.it
E-MAIL: info@fiatalba.it
C.FISC. e P.IVA 02713460042
C.C.I.A.A. 33986/1999



The Ultimate Hand-Held Refractometer Unsurpassed in Function, Operation, and Design

MASTER



Design Registration No.000379326-0001, 000379326-0002 (EU)
ZL 2005 3 0116403.4.5 (China), D111526 (Taiwan), D555, 549 (U.S.A.),
1255763, 1255764, 1255765, 1255766, 1255767 (Japan)
Patent Granted in countries around the world.

About the Trade Mark:
Year 2005-ATAGO was established 65 years ago and we have been developing, manufacturing, and marketing Refractometers based on our in-depth study of optics. This year we have released our NEW Hand-Held Refractometer series, the "MASTER" to support and meet our customer's needs. The NEW "MASTER" series is a fitting name to match its ultimate performance. The trade mark "AT" is the Japanese Kanji which means "light". The decision to use this Kanji as a trade mark for the MASTER series is to emphasize that this product was designed and manufactured in Japan. With the multitude of imitation products out in the market today, ATAGO is maintaining our identity as the master of manufacturing quality instruments. We, ATAGO, would like to be your business partner and to be the "light" to continue towards a bright future together.




Hand-held Refractometer

MASTER series

Choose the right model for your sample, based on the features and materials of the instrument.



Brix scale examples
MASTER-α Brix 0~33%




Features 6 types

Both the α and T types are equipped with the Automatic Temperature Compensation feature. Choose the α type for the added feature of IP 65 water-resistance. The H type is the heat-resistant version of the α type.


Series / Model	α	T	M	H	53S	500
Water resistant	●	—	—	●	●	●
Automatic temperature compensation	●	●	—	●	●	—
Heat resistant	—	—	—	●	—	●
Milky sample	—	—	—	—	●	—

MASTER-53S for Milky sample

Opaque, inhomogeneous liquids can be difficult to get a clear boundary line with a conventional refractometer. This model is recommended for cream-based sauces, yogurt, mayonnaise, and various emulsions used in industrial processing.



MASTER-500 0-90% Wide Brix Range



Understanding model names

A model name consists of the scale (sample name), material, and feature type.

Brix Scale

MASTER- 2 P α

Example Measuring sauces

Sample information

- About 40% Brix (see A in chart below)
- Salty
- Oily

Scale
Choose **2** 28-62% (see B in chart below).

Material
Choose the salt-resistant **P** plastic body.
Metal ... Blank

Features
Choose the washable type for easy cleaning.
Choose **α**

Material 2 types

Metal

Die-cast aluminum

Ideal for the agriculture industry, metal working fluids, and various high-temperature samples. Resistant to organic solvents.



Plastic

PBT (polybutylene terephthalate)

Resistant to salty and acidic samples.



Brix of Various Samples

Brix (%)	Food industry	Chemical industry	Medical Science industry	Memory (Brix)						
				(1)	10	20	53	500		
1.333	Drinks	Water	Methanol							
	Green tea	Saline	Saline	0	0	0	0	0		
	Beer	Fruits / Vegetables	Aloe extract	33	10	20	53	90		
		Seasonings	Sea water	%	%	%	%	%		
1.34		Miso soup	Nickel plate liquid							
	Tomato		Chlorella extract							
	Strawberry									
	Lemon									
1.35	Coffee		Gelatin liquid							
	Soy milk	Orange	Serum							
	Cola	Apple								
	Milk	Prince melon	Freon113							
1.35		Beef curry								
		Demiglace (sauce)								
		Orange jelly								
1.36	Lactic acid-bacteria beverage		Silicone solution (emulsion)							
			Acetone							
			Ethanol							
1.37		Canned syrup	Electrolyte							
			Freon 11							
1.38		Ketchup	Saturated saline							
1.39		Soy sauce								
		Sauce A								
1.40		Low-sugar jam								
1.40		Egg yolk	Silicone oil							
			Octane							
1.40										
50										
60	Fats		Ethylene glycol							
	Butter		Propylene glycol							
60										
70										
70										
80										
80										
90										
90										

Specifications

Brix Scale

Range (Minimum)	Series	α		T		M	
		Metal	Plastic	Metal	Plastic	Metal	Plastic
1 0 to 33% (0.2%)	Model	MASTER-α	MASTER-Pα	MASTER-T	MASTER-PT	MASTER-M	MASTER-PM
	Cat.No.	2311	2391	2312	2392	2313	2393
	Accuracy	±0.2% *±0.1% (10 to 30°C)		±0.2% *±0.1% (10 to 30°C)		±0.2% *±0.1%	
	Size & Weight	3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g	

Range (Minimum)	Model	MASTER-2α	MASTER-2Pα	MASTER-2T	MASTER-2PT	MASTER-2M	MASTER-2PM
		Cat.No.	2321	2941	2322	2942	2323
2 28 to 62% (0.2%)	Accuracy	±0.2% *±0.1% (10 to 40°C)		±0.2% *±0.1% (10 to 40°C)		±0.2% *±0.1%	
	Size & Weight	3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g	

Range (Minimum)	Model	MASTER-3α	MASTER-3Pα	MASTER-3T	MASTER-3PT	MASTER-3M	MASTER-3PM
		Cat.No.	2331	2951	2332	2952	2333
3 58 to 90% (0.2%)	Accuracy	±0.2% *±0.1% (10 to 40°C)		±0.2% *±0.1% (10 to 40°C)		±0.2% *±0.1%	
	Size & Weight	3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g	

Range (Minimum)	Model	MASTER-4α	MASTER-4Pα	MASTER-4T	MASTER-4PT	MASTER-4M	MASTER-4PM
		Cat.No.	2341	2961	2342	2962	2343
4 45 to 82% (0.2%)	Accuracy	±0.2% *±0.1% (10 to 40°C)		±0.2% *±0.1% (10 to 40°C)		±0.2% *±0.1%	
	Size & Weight	3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g	

Range (Minimum)	Model	MASTER-10α	MASTER-10Pα	MASTER-10T	MASTER-10PT	MASTER-10M	MASTER-10PM
		Cat.No.	2371	2981	2372	2982	2373
10 0 to 10% (0.1%)	Accuracy	±0.2% *±0.1% (10 to 30°C)		±0.2% *±0.1% (10 to 30°C)		±0.2% *±0.1%	
	Size & Weight	3.2x3.4x20.3cm, 155g		3.2x3.4x20.3cm, 155g		3.2x3.4x20.3cm, 155g	

Range (Minimum)	Model	MASTER-20α	MASTER-20Pα	MASTER-20T	MASTER-20PT	MASTER-20M	MASTER-20PM
		Cat.No.	2381	2991	2382	2992	2383
20 0 to 20% (0.1%)	Accuracy	±0.2% *±0.1% (10 to 30°C)		±0.2% *±0.1% (10 to 30°C)		±0.2% *±0.1%	
	Size & Weight	3.2x3.4x20.7cm, 165g		3.2x3.4x20.7cm, 165g		3.2x3.4x20.7cm, 165g	

Range (Minimum)	Model	MASTER-53α	MASTER-53Pα	MASTER-53T	MASTER-53PT	MASTER-53M	MASTER-53PM
		Cat.No.	2351	2971	2352	2972	2353
53 0 to 53% (0.5%)	Accuracy	±0.5% *±0.25% (10 to 30°C)		±0.5% *±0.25% (10 to 30°C)		±0.5% *±0.25%	
	Size & Weight	3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g		3.2x3.4x16.8cm, 130g	

Heat resistant

Series	H			
	Metal			
Model	MASTER-50H	MASTER-80H	MASTER-93H	MASTER-100H
Cat.No.	2354	2364	2374	2384
Range	Brix 0.0 to 50.0%	Brix 30.0 to 80.0%	Brix 45.0 to 93.0%	Brix 60.0 to 100.0%
Minimum	0.5%			
Accuracy	±0.5% *±0.25%			
Size & Weight	3.2x3.4x 16.8cm, 130g			

Milky sample Wide Brix

Series	53S	500
	Metal	
Model	MASTER-53S	MASTER-500
Cat.No.	2355	2363
Range	Brix 0.0 to 53.0%	Brix 0.0 to 90.0%
Minimum	0.5%	1.0%
Accuracy	±0.5% *±0.25%	±1% *±0.5%
Size & Weight	3.2x3.4x 16.8cm, 130g	

Special Scale

Sample	Coolant	Battery Coolant	Battery Coolant	Refractive index	Honey
	M	M	M	M	α
Material	Plastic	Plastic	Plastic	Metal	Plastic
Model	MASTER-BR	MASTER-BC	MASTER-BCF	MASTER-RI	MASTER-HONEY
Cat.No.	2930	2931	2932	2612	2524
Scale	① propylene glycol ② ethylene glycol	① ethylene glycol freezing temp ② propylene glycol freezing temp ③ battery fluid #20/20	① ethylene glycol freezing temp ② propylene glycol freezing temp ③ battery fluid #20/20	Refractive index	Honey moisture
Range	① 0 to 70% 0 to -50°C ② 0 to 70% 0 to -50°C	① 0 to -50°C ② 0 to -50°C ③ 1.150 to 1.300	① 32 to -60°F ② 32 to -50°F ③ 1.150 to 1.300	1.435 to 1.520	12.0 to 30.0%
Minimum Scale	5% 5°C	① 5°C ② 6°C ③ 0.01	① 10°F ② 10°F ③ 0.01	0.001	0.2%
Size & Weight	3.2x3.4x16.8cm, 130g				

Sample	Seawater	Seawater	Salinity	Salinity	Salinity (Wide range)	Salinity (Wide range)
	α	M	α	M	α	M
Material	Plastic	Plastic	Plastic	Plastic	Plastic	Plastic
Model	MASTER-S/MIll α	MASTER-S/MIll M	MASTER-S10 α	MASTER-S10 M	MASTER-S28 α	MASTER-S28 M
Cat.No.	2491	2493	2471	2473	2481	2483
Scale	① Salinity ② Specific gravity		Sodium chloride		Sodium chloride	
Range	① 0 to 100% ② 1.000 to 1.070		0.0 to 10.0g/100g		0.0 to 28.0g/100g	
Minimum Scale	① 1% ② 0.001		0.1g/100g		0.2g/100g	
Measurement Accuracy	① ±2% *±1% ② ±0.001 *±0.0005 (10 to 30°C)		±0.2g/100g *±0.1g/100g (10 to 30°C)		±0.2g/100g *±0.1g/100g (10 to 30°C)	
International Protection Class	IP65		IP65		IP65	
Size & Weight	3.2x3.4x20.7cm, 110g		3.2x3.4x20.3cm, 105g		3.2x3.4x16.8cm, 90g	

IP65 = dust-tight and protected against water jets (except eye piece)
*Repeatability

Sugar-Free Drinks

Diet Drinks

etc.

Specially developed for very low concentration solutions, Brix 8% or less!!

Hand-held Refractometer
(For very low concentration samples)

N-8α

Cat.No.2360



Applications

Food industry :

- Sugar-Free
- Diet drink
- very thin soup

etc.

Measuring Method



①Place a couple of drops of sample onto the prism.



②Close the day-light plate gently.



③Look through the eyepiece and measure the value.



Features

- Bright, High Contrast scale view
- Scale memory lines are wider for cleaner reading of the boundary line
- Requires just one or two drops of sample
- Quick & easy measurements

Specifications

Measurement range: Brix0.0 to 8.0%
Minimum scale : 0.1%
Dimensions : 4(W)×4(D)×21(H)cm
Weight : 260g

ATAGO CO.,LTD.

<http://www.atago.net/> overseas@atago.net

- ATAGO U.S.A., Inc.
- ATAGO INDIA Instruments Pvt.Ltd.
- ATAGO THAILAND Co.,Ltd.
- ATAGO BRASIL Ltda.
- ATAGO ITALIA s.r.l.
- ATAGO CHINA Guangzhou Co.,Ltd.
- ATAGO RUSSIA Ltd.
- ATAGO NIGERIA Scientific Co.,Ltd.

- TEL : 1-425-637-2107 customerservice@atago-usa.com
- TEL : 91-22-28544915, 40713232 customerservice@atago-india.com
- TEL : 66-21948727-9 customerservice@atago-thailand.com
- TEL : 55 16 3913-8400 customerservice@atago-brasil.com
- TEL : 39 02 36557267 customerservice@atago-italia.com
- TEL : 86-20-38108256 info@atago-china.com
- TEL : 7-812-777-96-96 info@atago-russia.com
- TEL : 234-707-558-1552 atagonigeria@atago.net

Headquarters: The Front Tower Shiba Koen, 23rd Floor
2-6-3 Shiba-koen, Minato-ku, Tokyo 105-0011, Japan
TEL : 81-3-3431-1943 FAX : 81-3-3431-1945



HACCP GMP GLP

ATAGO products comply with HACCP,GMP, and GLP system standards.

FIAT FORNITURE INDUSTRIAL
ARTICOLI TECNICI
TECNOLOGIE sas
CORSO NINO BIXIO, 16
12051 ALBA (CN)
TEL.0173 290898 - 366669
FAX 0173 365277
www.fiatalba.it
E-MAIL: info@fiatalba.it
C.FISC. e PIVA 02713460042
C.CIAA 33986/1999

* Specifications and appearance are subject to change without notice.